LoPro Series





Commercial Air Curtains

The Most Cost-Effective Environmental and Sanitation Barrier You'll Never See

MARS AIR CURTAIN BENEFITS

- REDUCES ENERGY COSTS AND CONSUMPTION
- CREATES EFFECTIVE ENVIRONMENTAL SEPARATION
- MAINTAINS INTERIOR BUILDING TEMPERATURES
- PROVIDES LOW OPERATIONAL COSTS
- MINIMIZES DIRT, DUST, AND FUMES
- PREVENTS FLYING INSECTS FROM INTRUDING
- OFFERS AN UNOBSTRUCTED VIEW, ENHANCING SAFETY

LOPRO SERIES FEATURES

- AESTHETICALLY PLEASING "LOW PROFILE" 8" DESIGN
- LOW NOISE LEVEL FOR QUIET OPERATION
- EASY TO INSTALL
- LOW MAINTENANCE
- NSF MODELS AVAILABLE (See NSF sheet for complete specifications.)

DOOR WIDTHS

25" to 144"

DOOR HEIGHTS

ENVIRONMENTAL SEPARATION up to 8'
FLYING INSECT CONTROL up to 7'

HEATING OPTIONS

ELECTRIC AND STEAM/HOT WATER

AVAILABLE IN FOUR COLORS

800.421.1266

www.marsair.com



...Over Every Door

LoPro Series Commercial Air Curtains



AVAILABLE COLORS



Obsidian Black (standard)



Section

Titanium Silver



Spartan Bronze

Typical Applications: Drive-Up Windows • Concession Stands • Small Receiving Doors • Walk-In Coolers • Entrance Doors



ASSOCIATION APPROVALS AND LISTING. All Mars Air Systems products are manufactured using the best materials and components available. They are crafted by highly skilled, experienced tradespeople. Our products must pass stringent quality control standards. Mars Air Systems products are reliable, durable, and meet the stringent listing or certification requirements of many organizations. Specifics vary depending on the model, options installed or application usage. For specifics and warranty information, please call factory for details. Mars reserves the right to make improvements and changes to specifications without notice.



DISTRIBUTED BY:



...Over Every Door

800.421.1266

www.marsair.com

14716 South Broadway Gardena, CA 90248

FLA SINGLE PHASE SOUND MODEL **WIDTH DOOR** WEIGHT NUMBER **OF DOOR** HEIGHT dBA (lbs) 1157 208V/230V LPV25/LPN25* 25" 7' - 8' 2.4 1.2/1.2 49 24 LPV28/LPN28* 28" 7' - 8' 2.4 1.2/1.2 49 25 LPV30/LPN30* 30" 7' - 8' 2.4 1.2/1.2 49 28 LPV36/LPN36* 36" 7' - 8' 2.4 1.2/1.2 49 35 LPV42/LPN42* 42" 7' - 8' 2.4 1.2/1.2 50 38 7' - 8' LPV48/LPN48* 48" 2.4 1.2/1.2 52 42 1.4/1.4 LPV60/LPN60* 60" 7' - 8' 2.6 53 51 LPV72/LPN72* 72" 7' - 8' 2.6 1.4/1.4 53 61 84" LPV84-2/LPN84-2* 7' - 8' 4.8 2.4/2.4 53 79 LPV96-2/LPN96-2* 96" 7' - 8' 4.8 2.4/2.4 53 87 108" 5.0 2.6/2.6 54 96 LPV108-2/LPN108-2* 7' - 8' LPV120-2/LPN120-2* 120" 7' - 8' 5.2 2.8/2.8 54 105 LPV144-2/LPN144-2* 144" 7' - 8' 5.2 2.8/2.8 54 125

^{*} LPN units are ETL Sanitation (NSF/ANSI 37) approved. Variable speed not available. Please refer to marsair.com under Submittals for complete technical information.