

SR 8000 SERIES RIGID TRAFFIC DOOR



Applications

The SR 8000 Series Rigid Traffic Door is designed for applications where pedestrian, cart or motorized hand traffic is used to transport goods in restaurant, retail and commercial applications.

Limitations

Not recommended for man ridden fork lift traffic or heavy wash down environments.

Features & Advantages

SR 8000 Series Rigid Traffic Door panels are constructed with a 3/4" thick plywood core and a choice of finishes forming a 7/8" overall panel thickness. Offered with full gaskets or non-gasketed.

SR 8000 - Door panels have stainless steel edge capping and are adhered on both sides with an anodized aluminum top and 48" high stainless steel impact plates.

SR 8100 - Door panels have stainless steel edge capping and are adhered on both sides with stainless steel.

SR 8200 - Door panels have stainless steel edge capping and are adhered on both sides with your choice of decorative laminate.

SR 8300 - Door panels have PVC edge capping and are adhered on both sides with textured ABS.

The SR 8000 Series operates on the CMI GFN Low Rise "V" Cam gravity hinging system complete with bottom hinge pin assembly.

Doors are custom built to your own specific requirements and can be ordered up to 48" x 96" for singles and pairs up to 96" x 96".

Standard vision panels are 9" x 14" durable, clear 1/4" acrylic set in black rubber molding and centered at 60" from the finish floor. Other configurations and sizes are available upon request.

Options & Colors

Optional spring bumpers, impact plates or lower hinge guards are recommended in applications where cart or motorized hand traffic exists. All add years to the life of your door without compromising the fit and finish.

The SR 8300 is available in your choice of ABS colors that include Red, Metallic Gray, Chocolate Brown, Beige, Black or White. Optional colors or color matches are available upon request.

The SR 8200 is available in many colors, patterns and finishes from your choice of plastic laminate manufacturer's.

Installation & Maintenance

The SR 8000 Series is conveniently packaged ready to install in existing or factory supplied frames. The package includes templates, drawings, easy-to-follow instructions and thread-forming fasteners.

Periodic cleaning with industrial soap or detergent and regular lubrication of moving parts is recommended.

Warranty

The SR 8000 Series carries a three-year hinging system warranty and one-year panel warranty against manufacturer's defects. All warranties stipulate correct installation and sizing requirements.

Order Fulfillment

Most orders are filled within a 3 to 4 week period. All orders are FOB Winnipeg. Prepaid freight is available at extra cost.

