# Bug Barrier® AUTOMATIC Roll-Up

### **AUTOMATIC OPERATION ~**

In-tube motor is rated at 4 amps, single phase 120 v. Constant contact switch activates motor. Door speed is approximately 12" per second. (See page #6 for High Cycle usage)

Maximum 16' wide and 14' high

Minimum width ~ 40"

Doors between 40" wide and 14' high receive 2" Snaptite™ tracks with Gateway's unique patented windbars. Windbars are made of wood wrapped in galvanized steel that remains flexible enough to pop out in case of impact or excessive wind. Head room required is 8".

Doors greater than 11' wide receive 4"
Snaptite™ tracks with wind stabilizer bars. Wind stabilizer bars are used for larger door openings to maintain greater strength and dependability. Features Aluminum bottom profile bar with cushioned edge and a bottom draft seal for positive floor contact. Breakaway feature is used in the bottom profile bar to help prevent damage to the door by accidental impact. Head room required is 18".

### **MOUNTING OPTIONS ~**

Header Mount, Face of Wall, Stand-Off Bracket Mount. Unit width is critical on all header mounted doors. All Bug Barriers® are manufactured to + or - 1/8" tolerance.

## **SCREEN~**

Standard green colors - other colors available. 17" x 11" high strength, vinyl coated polyester weave screen material. Windbars are reinforced in yellow safety vinyl.

# **OPTIONAL** ~

Track sides are interchangeable to create 2" or 4" deep guides.

One year warranty on parts and workmanship.



# **RESET SYSTEM ~**

Interlocking brush seal is incorporated at the top of the Snaptite™ tracks causing a reset system. Should the door be forced out of the tracks by accidental impact, the door is designed to reset back into the guides.

## **WEATHERSTRIPPING~**

Grey vinyl weatherstripping is angled to provide a tighter seal preventing bugs and insects easy access or entry.

# WIND STABILIZER ~

Wind stabilizer bars used for larger door openings to maintain greater strength and dependability.

