



Manual Roll-Up

Bug Barrier®

MANUAL OPERATION ~

Heavy duty spring loaded roll tube.

**Maximum size is 14' wide x 14" high.
Minimum width is 54" wide.**

Doors exceeding the 10' high will receive fiberglass windbars for added stability.

Doors 11' wide and over will require 4" deep Snaptite™ tracks.

MOUNTING OPTIONS ~

Header Mount, Face of Wall, Stand-Off Bracket Mount. Unit width is critical on all header mounted doors. All Bug Barriers® are manufactured to + or - 1/8" tolerance.

SCREEN ~

Standard green color - other colors available. 17 x 11 high strength, vinyl coated polyester weave screen material. Windbars are reinforced in yellow safety vinyl.

TRACKS ~

2" wide and 2" deep Snaptite™ aluminum tracks. Header mount will take up to 3-1/2" of side room on each side. Wall mount will take up to 6" of side room on each side including weatherstripping.

WEATHERSTRIPPING ~


Grey vinyl weatherstripping is angled to provide a tighter seal preventing bugs and insects easy access or entry.

Mounting Options (See Page 8 for Stand-Off Mount)

Header Mount
(Under Lintel)
(In-Jamb)



Wall Mount
(Face of Wall)



RESET SYSTEM ~

Interlocking brush seal is incorporated at the top of the Snaptite™ tracks causing a reset system. Should the door be forced out of the tracks by accidental impact, the door is designed to reset back into the guides.

HEAD ROOM ~

6" to 7" will be used for header mount application. 8" is needed above the door opening for wall mount application.

BREAKAWAY FEATURE ~

Unique patented windbars are made of wood wrapped with galvanized steel that remains flexible enough to pop out in case of accidental impact.

CHAIN FALL OPERATION ~

Ability to lift door without spring assistance or a motor.

One year warranty on parts and workmanship.

