


9300 LIFT READY SERIES



9300 LIFT READY

ROLLING GRILLES

Redesigned in every possible way to streamline the installation, saving time and money.

chiohd.com

C.H.I. 
ROLLING STEEL DOORS

The Door to Quality.

9300 LIFT READY SERIES



MODELS AND MATERIALS

LIFT READY PORTCULLIS Straight Grille Pattern



LIFT READY LABRYRINTH Brick Grille Pattern



LIFT READY PRISTINE Polycarbonate Panels



LIFT READY VENTANA Perforated Aluminum




Lift Ready's attached ratcheting charging arm makes winding the spring easy and safe. And the slotted headplates allow the barrel to drop in place, speeding installation.



Lift Ready's exclusive Smart-Lock System allows end-users to engage the lock at a convenient height and then close grille to the floor, the grille locks automatically.




Lift Ready's exclusive extruded aluminum telescoping support tubes make loading, unloading and installing a lighter and easier task.



3" deep guides with wool pile insert for quiet operation mount to special angles, telescopic supports or steel tubes.




5/16" aluminum hoods rods spaced 1-3/4" O.C. with spacer tubes on every other rod and vertical links on 9" centers [optional perforated or polycarbonate panel available.]




Motors for Lift Ready grilles are factory installed in the barrel and do not require side, top or front of coil room.

MOUNTING DETAILS



1. Between jamb mount
2. Lift Ready tube mount
3. Steel tube mount
4. Face of wall mount E - Aluminum
5. Face of wall mount Z - Aluminum
6. Face of wall mount E - Steel
7. Face of wall mount Z - Steel




[Wood, Steel or Masonry]




[Aluminum Tube with Telescopic Support]




[Wood or Steel - Angle Conceals Guide Screws]



[Wood or Masonry - Angle Conceals Guide Screws]



[Wood or Steel]



[Wood or Masonry]

VISIT YOUR DOOR PROFESSIONAL AT:



The Door to Quality.

1485 Sunrise Drive • Arthur, Illinois 61911 • tel 800.677.2650 • fax 217.543.5172